

Plastic Welding Equipment Butt Welders Specifications



Specifications

	63-160mm	90-250mm	160-315mm
Operating range	63-160mm	90-250mm	160-315
Operating voltage	220V	220V	220V
Thermoelement	1600W	2000W	2500W
Planing tool	710W	1000W	1000W
Operating temperature	0-299°C	0-299°C	0-299°C
Compatible Materials	PE PP PB PVDF	PE PP PB PVDF	PE PP PB PVDF

Components of the Machine

63-160mm	90-250mm	160-315mm
Frame	Frame	Frame
Manual Hydraulic System	Manual Hydraulic System	Manual Hydraulic System
Planing tool	Planing tool	Planing tool
Heating-plate	Heating-plate	Heating-plate
Reduction Liners (1set =8 pieces)	Reduction Liners (1set =8 pieces)	Reduction Liners (1set =8 pieces)
63mm 75mm	90mm 110mm	160mm 180mm
90mm 110mm	125mm 140mm 160mm	200mm 225mm
125mm 140mm	180mm 200mm 225mm	250mm 280mm
Wrench	Wrench	Wrench
Fittings Chuck	Fittings Chuck	Fittings Chuck

Code

Manual Hydraulic Welder	2551601	2552501	2553151
Electro Hydraulic Welder	2551602	2552502	2553152

Robust machine manufactured in China, improved in Australia

Features:

- Wheels & handles included
- Full reduction liner set included
- Self centering fittings chuck included
- End clamp welding (making it easy to assemble tees & fittings)
- Removable components

Options:

- Manual or electro hydraulic
- Data logger compatible